



MP1096SSW MULTI-PACK SOLUTION

Power, surge protection and USB charging solutions for home and office electronics

The Cyberpower MP1096SSW combo pack comes with one 10-outlet surge protector strip with USB, one five-outlet surge protector strip with USB, and one three-outlet wall-tap with USB.

TYPICAL APPLICATIONS

- Consumer Electronics
- Personal Computers
- Chargers

FEATURES - 10-OUTLET SURGE PROTECTOR

- AC Outlets: 10
- AC Outlet Type: NEMA 5-15R
- Surge Protection: 3600 Joules
- USB-A Ports: 1
- USB-A Output: 2.4A
- USB-C Ports: 1
- USB-C Output: 15W
- Cord Length: 4 ft.
- Plug Type: NEMA 5-15P
- Plug Style: flat
- Electrical Rating: 125V/15A/60Hz
- Connected Equipment Guarantee: \$300,000
- Warranty: 1-Year Limited Warranty

FEATURES - 5-OUTLET SURGE PROTECTOR

- Surge suppression: 500 J
- Outlet type: NEMA 5-15R
- Outlet quantity: 5
- Total USB Output: 15W
- USB-C charge ports: 1
- USB-C charge output: 15W
- USB-A charge ports: 1
- USB charge output: 2.4A
- Power cord length: 4 ft
- Plug style: Right-angle 45° offset
- Volts: 125 V
- Circuit breaker: 15 A
- EMI/RFI Filtration: Yes
- Warranty: 1-Year Limited
- Connected Equipment Guarantee: \$25,000

FEATURES - 3-OUTLET WALL-TAP

- Volts: 125 V
- Plug type: NEMA 5-15P
- Outlet type: 3 NEMA 5-15R
- USB-A charge ports: 4 (4.2-Amp)
- Lighted USB ports: Yes
- Warranty: 1-Year Warranty



MP1096SSW

MULTI-PACK SOLUTION

SPECIFICATIONS

	10-OUTLET	5-OUTLET	WALL-TAP
INPUT			
Plug Type	NEMA 5-15P	NEMA 5-15R	NEMA 5-15P
Plug Style	Flat	Right Angle, 45° Offset	Wall-tap
Cord Length	4 ft.	4 ft.	Wall-tap
OUTPUT			
Outlet Type	NEMA 5-15R		
Outlets - Total	10	5	3
Output Voltage	5 VDC		
USB Charge Ports	1 USB-A, 1 USB-C	1 USB-A, 1 USB-C	4 USB-A
USB-A Charge Port Output	2.4 A	2.4 A (shared)	4.2 A
USB-C Charge Port Output	15 W	15 W	3.4 A
SURGE PROTECTION & FILTERING			
Surge Suppression	3,600J	500J	
Clamping Voltage	600V (H-N, H-G, N-G)	800V (H-N)	
Response Time	<1 Nanosecond		
EMI/RFI Filtration	Yes	Yes	
Auto Shutdown (Safe Fail)	Yes	Yes	No
INDICATORS			
LED Indicators	Protected Grounded		
PHYSICAL			
Color	White		
Keyhole Mounting Slots	Yes	Yes	Wall-tap

	10-OUTLET	5-OUTLET	WALL-TAP
DIMENSIONS			
Product Dimensions (Width/Height/Depth) cm	9.4 x 4.09 x 28.04 cm	4.55 x 3.81 x 24.79 cm	11.3 x 8.94 x 4.9 cm
Product Dimensions (Width/Height/Depth) mm	94 x 41 x 280 mm	45 x 38 x 248 mm	113 x 89 x 49 mm
Product Dimensions (Width/Height/Depth) in	3.7 x 11.61 x 11.04 in.	1.79 x 1.50 x 9.76 in.	4.45 x 3.52 x 1.93 in.
Shipping Dimensions (Width/Height/Depth) cm	17.78 x 12.7 x 35.56 cm		
Shipping Dimensions (Width/Height/Depth) mm	177.8 x 127.0 x 355.6 mm		
Shipping Dimensions (Width/Height/Depth) in	7 x 5 x 14 in.		
Shipping Weight (kg)	1.45 kg		
Shipping Weight (lbs.)	3.20 lbs.		
CERTIFICATIONS			
Environmental	RoHS Compliant		
Safety	UL1363 UL1449 4th Edition UL1310 cUL	UL1449 3rd Edition UL1363 UL1310 FCC cUL DOE VI	UL498a 1310 cULI FCC DOE VI
WARRANTY			
Product Warranty	One-Year Limited Warranty		
Connected Equipment Guarantee	Lifetime	Lifetime	
CEG Amount	\$300,000	\$25,000	