

CyberPower

MP1089SSW MULTI-PACK SOLUTIONS

Protect home and office computers, electronics, and home theater equipment

The MP1089SSW Surge with USB 3-Pack safeguards common home and office devices, such as computers and electronics, by absorbing spikes in energy caused by storms and electrical power surges. All three units in the 3-pack provide surge protection — 1,500J for the 3-outlet wall-tap, and 500J for the 5-outlet strips. All three units have USB-A and USB-C ports, to give the ability to charge mobile, USB-enabled devices.

All three surge protectors feature metal oxide varistor (MOV) technology and come with One-Year Limited Warranties and Connected Equipment Guarantees.

TYPICAL APPLICATIONS

- Consumer Electronics
- Personal Computers
- Chargers

3-OUTLET SURGE PROTECTOR WALL-TAP WITH USB-A AND USB-C

- Surge Suppression: 1,500 J
- Plug Type: NEMA 5-15P
- Outlet Type: 3 NEMA 5-15R
- Total USB Output: 18W
- USB-C Charge Ports: 1
- USB-C Charge Output: 15W
- USB-A Charge Ports: 2
- USB Charge Output: 3.6A (shared)
- Volts: 125 V
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$100,000

5-OUTLET SURGE PROTECTOR STRIP WITH USB-A AND USB-C

- Surge Suppression: 500 J
- Outlet Type: NEMA 5-15R
- Outlet Quantity: 5
- Total USB Output: 15W
- USB-C Charge Ports: 1
- USB-C Charge Output: 15W
- USB-A Charge Ports: 1
- USB Charge Output: 2.4A
- Power Cord Length: 4 ft
- Plug Style: Right-angle 45° offset
- Volts: 125 V
- Circuit Breaker: 15 A
- EMI/RFI Filtration: Yes
- Warranty: One-Year Limited
- Connected Equipment Guarantee: \$25,000



MP1089SSW

MULTI-PACK SOLUTIONS

SPECIFICATIONS

	3-OUTLET WALL-TAP	5-OUTLET STRIP
INPUT		
Cord Length	Wall-tap	4 ft (1.2 m)
Plug Style	Three-Prong Direct Plug-in	Right Angle, 45° Offset Right
OUTPUT		
Outlet Type	NEMA 5-15R	
Outlets - Total	3	5
USB Charge Ports	Yes	
USB Charge Port Output	3.6 Amps (shared)	2.4 Amps
USB Charge Port Output	2 USB-A, 1 USB-C	2 USB-A, 1 USB-C
USB Charge Port Voltage	5 VDC	
SURGE PROTECTION & FILTERING		
Attenuation	32 dB	
EMI/RFI Filtration	150KHz 100MHz	
Response Time	< 1 Nanosecond	
PHYSICAL		
Color	White	
Form Factor	Wall-tap	Strip
Material of Construction	Plastic	

	3-OUTLET WALL-TAP	5-OUTLET STRIP
DIMENSIONS		
Product Dimensions (WxHxD) cm	10.31 x 14.76 x 4.72 cm	4.55 x 3.81 x 24.79 cm
Product Dimensions (WxHxD) mm	103 x 148 x 47 mm	45 x 38 x 248 mm
Product Dimensions (WxHxD) in	4.06 x 5.81 x 1.86 in.	1.79 x 1.50 x 9.76 in.
Shipping Dimensions (WxHxD) cm	24.0 x 32.41 x 8.99 cm	
Shipping Dimensions (WxHxD) mm	240.03 x 324.1 x 89.92 mm	
Shipping Dimensions (WxHxD) in	9.45 x 12.76 x 3.54 in	
Shipping Weight (kg)	1.22 kg	
Shipping Weight (lbs.)	2.70 lbs.	
CERTIFICATIONS		
Environmental	RoHS Compliant	
Safety	UL1449, UL1363, UL1310, cUL, FCC, DOE VI	
WARRANTY		
Product Warranty	One-Year Limited Warranty	
Connected Equipment Guarantee	Lifetime	